





















GIB® RONDO® METAL BATTEN SELECTOR

RONDO®

GIB® RONDO® 310	308 SYSTEM	129 SYSTEM
 12639 3.6m 12640 4.8m 12641 6.0m 310 Batten	 14918 3.6m 14919 4.8m 14920 6.0m 308 Batten	 14915 3.6m 14916 4.8m 14917 6.0m 129 Batten
 12711 311 Clip	 14903 226 Clip	
 14907 313 Long Clip	 14909 394 Long Clip	
 14209 A311 GIB Quiet Clip®	Resilient mount Direct fix to wall or ceiling Accepts 129 or 308 batten. Also referred to as ST001	 14984 STWC Acoustic Clip
 12643 312 Joints	 14924 138 Joints	
 12642 3.0m 340 Perimeter Channel	 14937 142 Perimeter Channel	 14936 140 Perimeter Channel
Can also be used for internal corners in tiled shower situations (see GIB® Site Guide)		
	 12645 3.0m NZ18 Perimeter Angle	

- Vertically Aligned Components are compatible.
- The long clips 313, 394 and 305 clips will provide approx. 100mm additional drop below ceiling framing.

Use the complete GIB® systems and enjoy complete peace of mind with proven solutions for NZ conditions and comprehensive nationwide after-sales service

SUSPENDED CEILING ACCESSORIES			
Fix vertically. 5mm galv. rod (121) is fitted by squeezing the two lugs of the 547 clip. Easily adjustable for height		14935 547 Clip	100 or 180mm bolt length (incl 30mm anchor) For direct fixing to concrete walls or ceilings Accepts 129 or 308 Batten 239 excl bolt, 237 excl bolt & threaded hole 14911 100mm Rod A239 Clip 14913 180mm Rod A239 Clip 14904 237 Clip
Fix horizontally. 5mm galv rod (121) is fitted by squeezing the two lugs of the 534 clip. Easily adjustable for height		14934 534 Clip	For direct fixing to concrete walls or ceilings. Approx 25mm adjustment for height in 5mm increments Accepts 129 or 308 Batten 14914 BETAFIX Clip
5mm galv. rod		14931 3.6m 121 Rod	Direct horizontal fixing to timber or steel framing Accepts 127 or 128 TCR 14902 166 Clip
Friction fitted to 121 rod Connects to TCR		14930 2534 Clip	Ceiling resilient mount Fits into 127 or 128 TCR. Accepts either 129 or 308 battens 14983 STSU Clip
Top Cross Rail (TCR) Also called a strongback. Clips to 2534 clip 127-25mm, 3.6, 4.8m 128-38mm, 4.8m		14921 3.6m 14922 4.8m 127 TCR 14923 4.8m 128 TCR	Side mount clip - low profile alternative for 2534 clip Connects 127 TCR to 5mm rod. Provides height adjustment 14929 167 Clip
Clicks into TCR at spacings to suit the ceiling lining, ie. 450mm for 10mm plasterboard and 600mm for 13mm plasterboard Connects to 308 or 129 batten		14925 139 Clip	MISCELLANEOUS COMPONENTRY Provides plasterboard fixing to structural steel framing in conjunction with 140 Perimeter channel 15007 BMCL Clip Fix directly to studs as per GIB® Noise control systems literature 11163 2.4m 11164 3.0m GIB RAIL®
28mm deep Fits into 139 clip		14915 3.6m 14916 4.8m 14917 6.0m 129 Batten	
16mm deep Fits into 139 clip		14918 3.6m 14919 4.8m 14920 6.0m 308 Batten	

For more information call the GIB® Helpline **0800 100 442** or visit **www.gib.co.nz**

